



COD	Ø	mm	Str	Box
FA1117	47	180	STL8C ø8 roller sleeve ricambio estraibile t8	60
		200	RR roller cover ricarica	60
		230		
		250	STLMA8C with ø8 stick frame con manico t8	40

TEXTURED POLYAMIDE 11

Continuous filament



high wear resistance
industrial use
slightly textured coverage

Material = **polyamide**

Pile = **short 11 mm**

Short pile paint roller made of continuous filament curly polyamide. Professional paint roller for industrial and shipbuilding application; ideally suited for levelling, restore or protective coating on plaster and damaged or uneven wall surfaces. The curling and waving warp maintains shape and volume during application and results a plaster-like rough texture.

Intended use

Polyester, polyurethane or epoxy resins and glues, medium density primers and base-paints, varnishes high in elastomers.

Paints

INSULATOR
FIXATIVE
GRABBING
ELASTOMERIC COATING
SATIN RESIN
SILOXANE

Surfaces

PLASTERING MORTAR
PLASTERWORK
GYPSUM
DRYWALL
LIME-CEMENT
PREFAB

NYLON BCF TESTURIZZATO 11

Filo continuo



alta resistenza a usura
uso industriale
texture leggermente bucciata

Materiale = **nylon**

Pelo = **corto 11 mm**

Rullo a pelo basso in poliammide a filo continuo testurizzato. Rullo professionale per uso industriale e cantieristico, ideale per rivestimenti uniformanti, protettivi o di ripristino su intonaco e superfici murali degradate o incoerenti. La fibra grettata e ondulata mantiene forma e volume durante la rullata e realizza una texture rugosa che imita l'effetto dell'intonaco civile.

Destinazione d'uso

Colle e resine poliesteriche, poliuretaniche o epossidiche, primer e pitture base a media diluizione, vernici ad alto contenuto di elastomeri.

Vernici

ISOLANTI
FISSATIVI
AGGRAPPANTI
PITTURE ELASTOMERICHE
RESINE OPACHE
SILOSSANICI

Superfici

INTONACO A MALTA
INTONACO A TEMPERA
CALCE-CEMENTO
PREFABBRICATO
CARTONGESSO
GESSO